

Chopped Strand For BMC (Bulk Molding Compound)

Reinforcement for thermoset molding compounds used in compression molding applications.

SIZING	FIBER LENGTH (MM)	FILAMENT DIAMETER (μm)	HIGH PERF.	GAL PURP.	PHENOLICS & FRICTION MATERIALS	UNSATURATED POLYESTER & EPOXY	AVAILABILITY
979 Indirect CS	3.6 & 12	14		X		X	Europe
R63 Indirect CS	3.6 & 12	14	X		X		
101C Indirect CS	3.6 & 12	13	X			X	
P316 Direct CS	3.6 & 12	17		X		X	
914 Direct CS	4.5	14	X		X		
5349 Indirect CS	3 & 6	11	X		X		
D55102-13C Direct CS	3.2, 6.4 & 13	13		X		X	North America
CS 405B	3.2, 4.7, 6.4 & 13	13		X	X	X	South America
DS 5407-17R	3.2, 6.4	17		X	X	X	
979 Indirect CS	3, 6, 9 & 12	14		X		X	China
979	3, 4.5, 6 & 12	14		X		X	India
P 546	3, 4.5, 6 & 12	13.5		X	X		India
P526	6 & 12	13.5			wet usage		
101C Indirect CS	3.6 & 12	13		X	3mm	X	Korea